			Ψ		
		· · · · · · · · · · · · · · · · · · ·		·	
	SC-6 Reversible Tip			661-XXX	
				Available in the following sizes* :	
		Applications	Features & Benefits	211 225 323 419 513 527	
		• Buildings	New ergonomic design assures comfort when rotating to any comparison of the characteristic for the comparison of the characteristic of the characteristeristic of the characteristic of the characteristeristeristi	213 311 325 421 515 529	
		Houses	to spray or reverse position for cleaning	<u>215 313 331 423 517 531</u>	
		• Bridges • Tanks	 Exclusive flow indicator indicates that tip is in spray or clean position 	<u>217 315 411 425 519 533</u> 219 317 413 427 521	
			 Highest quality tungsten carbide assures longest life, 	221 319 415 431 523	
			durability, and Fewer passes for better coverage	223 321 417 511 525	
				* See accessory catalog for additional sizes	
	SYNERGY M			671-XXX	
	SYNERGY M	<u> </u>		077-XXX	
	200-	<i>Applications</i>	Features & Benefits	Available in the following sizes:	
		• Cabinets	• Particle size up to 27% smaller than a standard tip.	208 210 212 214 308 310 312 314	
		• Shutters	 Interchangeable with industry standard bases. 	408 410 412 414	
		• Doors	• Increase standard reversible tip life by 80%.	510 512 514	
		• Trimwork		612 614	
	Line Striping Tip			665-XXXX	
		Applications	Features & Benefits	Available in the following sizes:	
		• Parking Lots	 The SC-6[™] Reversible Striping Tip used with the 	1302 1702 2112 2712 3512	
		Developments	proper spraying pressure and speed, virtually eliminates	1304 1704 2308 2908 3908	
		Athletic Courts/Fields	jagged lines caused by excessive edge paint.	1308 1708 2312 2912 3912	
		Stencils	 Features Titan's proprietary "Extended Life" tungsten carbide proven to outlast competitive tips by 20%. 	1502 1904 2508 3108 4308 1504 1908 2512 3112 4312	
1			 Each tip is precision ground to apply paint at an even 	1504 1906 2512 5112 4512 1508 2108 2708 3508	
			mil thickness across the width of the line.		
+					
	WideSpray [™]			661-XXXX	
	2004	Applications	Features & Benefits	Available in the following sizes:	
		• Commercial Buildings	Perfect for high production applications	1219 1223 1227 1231 1235	
		Convention Centers	• Increase production up to 100%	1221 1225 1229 1233 1237	
		Warehouses	• Widespray will save you time and money		
		 Track Housing 			
	Flat Tip			002-XXX	
		Applications	Features & Benefits	Available in the following orifice sizes:	
		• Ship Yards	Precision machined from the highest quality	007 013 021 035 052	
		• Knock Down	Tungsten Carbide	009 017 026 039	
		• Swimming Pools	• Available in sizes from .007072	011 019 031 043	
		• Roofing	Gasket not included	* See accessory catalog for additional sizes	
	Adjustable Self-Cleaning Tip			241 VVV	
	Aujustable Self-Cleaning Th			341-XXX	
		Applications • Office Complexes • Convention Centers • Ship Yards • Undercoatings	Features & Benefits	Product Number Orifice Range	
			• Fully adjustable fan widths from 2" to 24" reduce overspray	341-015 .005018	
			• Self-cleaning feature eliminates costly downtime due to clogs	<u>341-020</u> .007019 341-024 .007026	
			Tungsten carbide wear parts for long life	341-028 .011026	
				341-041 .017035	

Titan Airless Tip Selection





Longest Lasting Tips In The Industry

Solvent Proof Seal

 \oplus

- Hand-tite design on the SC-6 series
- Highest quality tungsten carbide assures longest life and durability
- Fewer passes and better coverage than competitors because of full fan pattern with minimal feathering
- SC-6 insertion and knockout tool for no fuss assembly
- SC-6 ergonomic handle design
- SC-6 flow indicator
- SC-6 one seal and retainer for all coatings

Adjustable and Flat Tip Safety Guard and Spec Chart

450-100A	7/8″-14	Titan, Wagner, Graco, Spray TECH, ASM
450-300	11/16″-16	Speeflo, ASM, Spray TECH, Taiver

SC-6 Safety Guard Chart

661-012	7/8″	SC-6 Guard Titan, Wagner, Graco,	
001 012	110	Spray TECH, ASM	
661-015	11/16″-16	SC-6 Guard #3 Speeflo, ASM,	
		Spray TECH, Taiver	
661-016	3/4″-20	SC-6 Guard #8 (Binks)	











SC-6









Line Striping







